

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problems Mailbox.**


**THIS PAGE BLANK (USPTO)**



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : <b>H04L 12/56, 29/08, H04Q 11/04, 7/22</b>		<b>A1</b>	(11) International Publication Number: <b>WO 00/21253</b>
			(43) International Publication Date: 13 April 2000 (13.04.00)
(21) International Application Number: PCT/FI99/00821 (22) International Filing Date: 5 October 1999 (05.10.99) (30) Priority Data: 982167 6 October 1998 (06.10.98) FI (71) Applicant (for all designated States except US): NOKIA NETWORKS OY [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI). (72) Inventor; and (75) Inventor/Applicant (for US only): RINNE, Mikko, J [FI/FI]; Tallbergin puistotie 1 C 25, FIN-00200 Helsinki (FI). (74) Agent: KOLSTER OY AB; Iso Roobertinkatu 23, P.O. Box 148, FIN-00121 Helsinki (FI).		(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  <b>Published</b> With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	

(54) Title: A DATA SEGMENTATION METHOD IN A TELECOMMUNICATIONS SYSTEM



## (57) Abstract

In a telecommunications system a larger higher layer data unit (SDU) is segmented into smaller segments on the lower layer (RLC). A segmentation length information is used to indicate the lengths of the segments in a lower layer protocol data unit (PDU). Specific values of segmentation length information are employed to indicate, when necessary, special information about the upper layer data unit (SDU), such as whether the upper layer data unit ends in the current data segment in the lower layer PDU or continues to the next lower layer PDU. This information is needed in the receiver to correctly assemble the segmented data.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## A data segmentation method in a telecommunications system

### Field of the Invention

The invention relates to data segmentation in a data transmission or  
5 signalling in telecommunications systems, and particularly in wireless telecommunications systems.

### Background of the Invention

Wireless communications system refers generally to any telecommunications system which enable a wireless communication between the users and the network. In mobile communications systems users are capable of  
10 moving within the service area of the system. A typical mobile communications system is a Public Land Mobile Network (PLMN).

At present third generation mobile systems, such as Universal Mobile Communication System (UMTS) and Future Public Land Mobile Telecommunication System (FPLMTS) later renamed as IMT-2000 (International Mobile Telecommunication 2000), are being developed. The UMTS is being  
15 standardized in ETSI (European Telecommunication Standards Institute) whereas ITU (International Telecommunication Union) is defining the IMT-2000 system. The radio interface is likely to be based on a wideband CDMA (code division multiple access), and therefore the third generation systems are  
20 often referred to as Wideband CDMA systems (WCDMA). These future systems are basically very much alike.

Fig. 1 shows a simplified UMTS architecture with the external reference points and interfaces to the UMTS Terrestrial Radio Access Network, UTRAN. The UTRAN consists of a set of Radio Access Networks RAN (also called Radio Network Subsystem RNS) connected to the Core Network CN through the interface Iu. These Radio Network Subsystems can be interconnected through the interconnection point (reference point) Iur. The interfaces  
25 Iu(s) and Iur are logical interfaces. Iur can be conveyed over physical direct connection between RANs or via any suitable transport network. Each RAN is responsible for the resources of its set of cells. For each connection between a mobile station MS and the UTRAN, one RAN is the Serving RAN. A RAN consists of a Radio Network Controller RNC and a multiplicity of base stations BS.  
30 The RNC is responsible for the handover decisions that require signalling to the MS. The base stations are connected to the RNC through the Iub inter-

face. The core network CN is a conventional or future telecommunication network modified to efficiently utilize the UTRAN in a wireless communication. Telecommunication networks that are thought to be suitable core networks are second generation mobile communication systems (PSTN), such as GSM, ISDN (Integrated Services Digital Network), B-ISDN (Broadband ISDN), PDN (Packet Data Network), ATM etc.

Fig. 2 gives an overview of the assumed protocol environment in the third generation systems. Categorically, we can find three layers of the ISO/OSI layer model (International Standards Organisation/Open Systems Interconnection): physical layer (Layer 1, L1), data link layer (Layer 2, L2), and network layer (Layer 3, L3). In Fig. 2 the Layer L3 includes Radio Resources Control (RRC) protocol and upper user plane protocols. RRC takes care of all radio resources management. It negotiates quality of service QoS for a bearer service and on the basis thereof chooses needed transport format(s), (bitrates, type of coding, physical layer multiplexing), performs allocations (codes etc.), allocates identifiers for MS:s and bearer services, signals all of these parameters to MS, and supervises all handovers. User plane protocols relate to any upper layer transmission and signalling protocols. As used herein the term L3 protocols may also include the Link Access Protocol LAC set up between the MS and the core network CN although LAC may also be said to be an L2 protocol. LAN provides a peer-to-peer transportation of user data.

Layer L2 functions include the Radio Link Control (RLC) protocol and the Medium Access Control MAC. The RLC provides a radio-solution-dependent reliable link over the radio path. It takes care of segmentation and assembly of the Layer 3 data before and after transmission over the radio path, respectively, as well as retransmissions. Under the RLC the MAC function controls the mapping of the RLC protocol data units (RLC PDUs) into physical channels in the physical layer. The physical layer includes all the schemes and mechanisms used to make communications possible on the radio channel. These mechanisms include, for example, modulation, power control, coding and timing.

The RLC is capable of segmenting the higher layer PDUs. The segmenting allows a larger higher layer (e.g. L3, LAC) data unit to be split into smaller units (segments) on the lower layer (RLC). When segmenting is used, the transmitting end should indicate to the receiving end whether the same higher layer unit will continue in the next lower layer unit or a new higher level

unit one will be started in the next lower layer unit. This information is needed in the receiver (either the mobile station (MS) or the network (NW)) to correctly assemble the segmented data.

5 In a prior art approach, a separate indicator has been used in each lower layer data segment to specify, whether the higher layer unit starts, ends or continues in the present data segment. Possible values may be the following, for example: 11 start & end; 10 start & continue; 00 continue; and 01 continue to end. The disadvantage of the prior art approach is that this extra field uses extra space in the protocol signalling and thereby causes extra overhead.

10

### Disclosure of the Invention

An object of the present invention is a segmentation method in which the overhead and other loss of performance caused by the segmentation information is minimized.

15

A first aspect of the invention is a data segmentation method in a telecommunications system, comprising the steps of

20

segmenting larger data units of a higher layer into smaller protocol data units (PDU) of a lower layer so that each lower layer PDU comprises one or more data segments each containing data from a different one of the upper layer data units,

providing the lower layer protocol data units containing two or more data segments, with a segmentation length information which indicates the length of the data segments,

25 indicating with predetermined values of the segmentation length information special information about the higher level PDU,

transmitting the lower level PDUs to a receiving end,

assembling the segmented higher level data unit at the receiving end by means of the segmentation length information.

30 A second aspect of the invention is a telecommunications system, comprising

an upper protocol layer comprising data units,

a lower protocol layer comprising protocol data units having a payload size smaller than said upper layer data units,

35 means segmenting said upper layer data units for insertion into smaller protocol data units of a lower layer so that each lower layer PDU comprises one or more data segments each containing data from a different one of

the upper layer data units,

means for inserting a segmentation length information which indicates the length of the data segments at least in the lower layer PDUs containing two or more data segments,

5 means for giving a predetermined value in the segmentation length information in order to provide a receiver with special information about the higher level data unit,

means for assembling the segmented higher level data unit from received lower layer PDUs at the receiver by means of the segmentation length information in said PDUs.

10 In the present invention specific values of segmentation length information are employed to indicate, when necessary, special information about the upper layer data unit, such as whether the upper layer data unit ends in the current data segment in the lower layer PDU or continues to the next lower layer PDU. Thus, a separate indicator field used in the prior art is avoided.

### Brief Description of the Drawings

In the following the invention will be described in greater detail by means of the preferred embodiments with reference to the accompanying drawings, in which

Figure 1 shows a simplified UMTS architecture,

Figure 2 illustrates an example of the protocol structure which may be used in the UMTS system,

Figure 3 illustrates the structure of the RLC protocol data unit (PDU),

Figures 4A, 4B and 4C illustrate the splitting of the upper layer service data unit (SDU) into payload units (PU) and the packing of the PUs in the RLC PDUs, and

Figure 5 illustrates a PU format with segmentation length indicators.

### Preferred Embodiments of the Invention

The preferred embodiments of the invention are in the following described as implemented in the UMTS system. The invention is applicable to be used in any telecommunication system requiring segmentation of larger upper protocol layer data units into smaller units on a lower protocol layer.

As used herein the term segmentation means splitting a larger data



unit of the higher layer (e.g. L3, LAC) into smaller units (segments) which can be accommodated by the lower layer (RLC) protocol data units (PDU). As a consequence, a data field of a lower layer PDU may contain one segment of an higher layer data unit, or two or more segments each containing data from a different one of the upper layer data units or padding. Segmentation information in a lower layer PDU is needed when the current upper layer data unit ends and a new upper layer data unit starts or padding is needed in the lower level PDU. The segmentation information is information included in the lower layer protocol unit in order to indicate to the receiving end how this segmentation, if any, in the PDU is done.

Examples of the architecture and the simplified protocol structure of a UMTS access network were described above with reference to Figs. 1 and 2, respectively.

The RLC can operate in assured, unassured and transparent modes. In the transparent mode no overhead is added to the data and no upper layer segmentation is maintained. In the assured and unassured modes segmentation and assembly of the upper layer PDUs is maintained. In the assured mode selective retransmission ARQ is also utilized to correct errors.

In the assured mode the RLC PDU has a control header and a data part consisting of one or more payload units (PU), as shown in Fig.3. The PU is the smallest unit of a retransmission protocol used between the transmitting end and the receiving end for error correction. The retransmission is based on an acknowledgement of PUs and/or sending retransmission requests for missing or distorted PUs by the receiving end. The size of the PU is constant, radio bearer specific, and it is determined in the L3 bearer setup negotiation. The size of the PU can be changed only through an L3 bearer reconfiguration. Several PUs are utilized for high data rates if also low data rates need to be served or if a tight raster of bit rates is required.

The normal control header includes a 14-bit sequence number (SN) of the first payload unit in the PDU and two 1-bit extension flags, E and D. If the extension flag E is set, an extended header is used, i.e. the next two octets contain a new sequence number SN with a new extension flags E and D. The second extension flag D is used to indicate that the PU referenced by the respective sequence number start with segmentation information. The SN field indicates the sequence number of a payload unit PU in the RLC PDU. In normal assured-mode RLC PDU header it is the sequence number of the first PU

in the PDU. If the PUs are not in sequence, a sequence number may be indicated separately for each PU by using the extended header. Also if some other than the first PU contains the segmentation information, the sequence number of the respective PU(s) is indicated separately by using the extended header.

5 If only the first PU in the RLC PDU contains the segmentation information the extension flag D in octet 2 of the PDU header is set (the first SN refers to the first PU). If several PUs contain the segmentation information in the PDU, each such PU is indicated in the PDU header by means of the respective PU sequence number with the D flag set. If no PU in the RLC PDU contains the segmentation information, no D flag is set in the PDU header.

10 Figs. 4A and 4B illustrate how the upper layer (e.g. L3, LAC) data unit 41, called service data unit SDU herein, is split into smaller units 42, i.e. payload units PU. The border between two consecutive SDUs may be aligned with a border between two consecutive PUs, as shown in Fig. 4B, or it may occur in the middle of PU. The PUs 42 are then packed into RLC PDUs, as illustrated in Fig. 4C. In accordance with the terminology used herein, RLC PDU1 in Fig. 4C contains only one data segment, i.e. each of the n PUs contain data only from one upper layer data unit, namely SDU1. However, the RLC PDU2 in Fig. 4C contains two data segments, i.e. PUs n-5...n contain data from the SDU1 and thereby provides the first data segment, whereas PUs from n+1 forwards contain data from the SDU2 and thereby provides the second data segment.

25 The segmentation information is provided by a variable number of length indicators that are included in at least one PU when needed. Length indicator is a (e.g. 7-bit) value the primary purpose of which is to indicate the length of the data segment in terms of octets (8 bits). However, all PUs in an RLC-U PDU do not need to have segmentation fields. The length indicator, for example 7-bit field, is assumed to be able to address all segments across the whole RLC PDU and therefore length indicators are normally included only in the first PU of an RLC PDU. This due to the fact that the maximum size of an RLC-U PDU data segment (approx. 40 octets) is expected to be much less than the maximum number addressable by the length indicator (128 octets). Also, it is mandatory that the length of the PDU and PU are known to both the transmitter and the receiver. The PU length is known from L3 service parameters and the RLC PDU length is recognized by receiving Layer 1 entity.

30  
35

Fig. 5 illustrates a PU format with N length indicators in the first PU. The total number of segments is O, each being M octets in length. The flag E in the length indicator indicates whether there is another length indicator in the following octet (flag E = 1) or not (flag E = 0).

5           In the most simple case, where the PU contains data only from one SDU, and no segmentation information is needed in the PU. In other words, a PU without any segmentation information means that the PU is contiguous, comes from one SDU and the same SDU continues until the next PU which contains a segmentation information. No separate indicator for indicating  
10 whether the SDU continues or not is needed. If all PUs in the RLC PDU contains data from the same SDU, no segmentation information is needed in the PDU. Alternatively, the first PU in the PDU may be provided with a length indicator having a predefined value which indicates that the SDU in this PDU continues in the next RLC PDU. Such a value may be 1111110, for example. If  
15 the SDU ends at end of the current PDU, this indicated by a length indicator value which points exactly to the end of the PDU.

          In the second situation the current SDU does not fill the PU completely and data from the next SDU is inserted into the remaining space in the PU. The first PU is provided with a length indicator giving the number of octets  
20 which contain data from the current SDU, i.e. the length indicator indirectly points the octet where the current segment and SDU ends. The flag E associated with the first length indicator is also set 1 to indicate that there is another length indicator. If the new SDU continues to the next PDU, a specific value, such as 11111110, is used for the second length indicator to indicate this. If  
25 the new SDU ends at end of the current PDU, this indicated by a length indicator value which points exactly to the end of the PDU.

          In the third case the current SDU ends in the PDU and, since there is not more SDUs in the transmitter buffer, the rest of the PDU or part of it contains padding (fill bits). Again, the first PU is provided with a length indicator giving the number of octets which contain data from the current SDU, i.e.  
30 the length indicator indirectly points the octet where the current SDU ends. The flag E associated with the first length indicator is also set 1 to indicate that there is another length indicator. The second length indicator is provided with a specific value, such as 1111111, to indicate that there is padding until the  
35 next length indicator occurs (in the same or next PDU).

By using and interpreting some specific values of the length indicator according to the above rules, for example, no separate indicator for noting whether the SDU continues or not is needed.

5 An alternative way for the use of specific values of the length indicator for noting continuation or end of the SDU, might be to use one bit in the length indicator for that purpose. This approach would have a disadvantage, however. When a segmentation length indicator is used, the length of the longest possible data segment depends greatly on the number of bits that can be accommodated in one length indicator. From implementation point of view,  
10 it is desirable to maintain octet alignment, and therefore the size of the length indicator is limited by the number of extra information that needs to be accommodated in the same octet. With 7 bits, a segment of 128 octets can be addressed, as noted. If one bit is stolen to the end-indication purposes, only  
15 of the length indicator as described above also this disadvantage will be avoided.

The application has above been described by means of the preferred embodiments to illustrate the principles of the invention. Regarding the details the invention may vary within the scope and spirit of the accompanying  
20 claims.

## Claims

1. A data segmentation method in a telecommunications system,  
**c h a r a c t e r i z e d** by the steps of  
segmenting larger data units of a higher layer into smaller protocol  
5 data units (PDU) of a lower layer so that each lower layer PDU comprises one  
or more data segments each containing data from a different one of the upper  
layer data units,  
providing the lower layer protocol data units containing two or more  
data segments, with segmentation length information which indicates the  
10 length of the data segments,  
indicating with predetermined values of the segmentation length  
information special information about the higher level PDU,  
transmitting the lower level PDUs to a receiving end,  
assembling the segmented higher level data unit at the receiving  
15 end by means of the segmentation length information.
2. The method as claimed in claim 1, **c h a r a c t e r i z e d** by said  
special information including indication whether the higher layer data unit ends  
in the current data segment or continues to the next lower level PDU
3. The method as claimed in claim 1 or 2, **c h a r a c t e r i z e d** by  
20 the step of  
indicating with a predetermined value of the segmentation length  
information that the rest of the lower level PDU contains padding until the next  
segmentation length information or to the next lower level PDU.
4. The method as claimed in claim 1, 2 or 3, **c h a r a c t e r i z e d**  
25 by the step of  
indicating with the segmentation length information pointing exactly  
to the end of the lower layer PDU that the higher layer data unit ends.
5. The method as claimed in claim 1, 2, 3 or 4, **c h a r a c t e r -**  
**i z e d** by the step of  
30 indicating with a predetermined value of the segmentation length  
information that the higher layer data unit carried in the current data segment  
continues to the next lower level PDU.
6. The method as claimed in any one of claims 1-5, **c h a r a c -**  
**t e r i z e d** by the step of  
35 providing no segmentation information in a lower layer PDU which  
contains data only from a single one of the higher layer data units and contain

no padding.

7. The method as claimed in any one of claims 1-6, **characterized** by the step of

5 providing segmentation information in a lower layer PDU which contains data only from a single one of the higher layer data units and padding.

8. The method as claimed in any one of claims 1-7, **characterized** by the steps of

10 providing each lower level PDU with two or more payload units of a predetermined length, the payload unit being the smallest unit in a retransmission protocol employed,

carrying said segmented higher layer data units in said payload units,

15 providing a segmentation indicator field in the beginning of one or more of the payload units in the lower level PDU, if required,

indicating in the header of the lower layer PDU which one or ones, if any, of the payload units contain the segmentation length information.

9. The method as claimed in any of claims 1-8, **characterized** by the step of

20 providing a segmentation indicator field in the beginning of the first one of the payload units for indicating segmentation information for all segments in the lower level PDU, if required.

10. A telecommunications system, **characterized** by  
25 an upper protocol layer (L3, RRC;LAC) comprising data units (SDU),

a lower protocol layer (L2, RLC) comprising protocol data unit (PDU) having a payload size smaller than said upper layer data units (SDU),

30 means segmenting said upper layer data units (SDU) for insertion into smaller protocol data units (PDU) of a lower layer so that each lower layer PDU comprises one or more data segments each containing data from a different one of the upper layer data units (SDU),

means for inserting a segmentation length information (LI) which indicates the length of the data segments at least in the lower layer PDUs containing two or more data segments,

35 means for giving a predetermined value in the segmentation length information (LI) in order to provide a receiver with special information about the

higher level data unit (SDU),

means for assembling the segmented higher level data unit (SDU) from received lower layer PDUs at the receiver by means of the segmentation length information in said PDUs.

5           11. The system as claimed in claim 10, **characterized** by a predetermined value of the segmentation length information (LI) indicating to the receiver that the rest of the lower level PDU contains padding until the next segmentation length information or to the next lower level PDU.

10           12. The system as claimed in claim 10 or 11, **characterized** by a predetermined value of the segmentation length information (LI) indicating to the receiver that the higher layer data unit (SDU) carried in the current data segment continues to the next lower level PDU.

15           13. The system as claimed in claim 10, 11 or 12, **characterized** by segmentation length information (LI) pointing exactly to the end of the lower layer PDU being defined to the receiver that the higher layer data unit (SDU) ends.

          14. The system as claimed in any one of claims 10-13, **characterized** by

20           two or more payload units (PU) of a predetermined length in each lower level PDU with two or more payload units of a predetermined length for carrying said segmented higher layer data units (SDU), the payload unit being the smallest unit in a retransmission protocol employed,

          a segmentation indicator field (LI) in the beginning of one or more of the payload units in the lower level PDU, if required,

25           at least one indicator (D) in the header of the lower layer PDU for indicating which one or ones, if any, of the payload units (PU) contain the segmentation length information (LI).

1/2

Fig. 1





Fig. 2





2/2




Fig. 3

Fig. 4A




Fig. 4B




Fig. 4C




Fig. 5

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 99/00821

## A. CLASSIFICATION OF SUBJECT MATTER

IPC7: H04L 12/56, H04L 29/08, H04Q 11/04, H04Q 7/22  
According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: H04L, H04Q, H04J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5570362 A (TAKASHI NISHIMURA), 29 October 1996 (29.10.96), column 2, line 9 - line 35; column 5, line 29 - line 36; column 6, line 32 - column 7, line 35, figures 4A,7,8A, claims 1-36	1,8,10
A	--	2-7,9,11-14
X	WO 9738550 A1 (TELEFONAKTIEBOLAGET LM ERICSSON (PUBL)), 16 October 1997 (16.10.97), page 10, line 22 - page 13, line 23, figures 7A,7B,7C,8, claims 1-45	1,8,10
A	--	2-7,9,11-14

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"I" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&amp;" document member of the same patent family

Date of the actual completion of the international search

15 February 2000

Date of mailing of the international search report

16 -02- 2000

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Erik Johannesson/CL

Telephone No. +46 8 782 25 00

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 99/00821

## C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5583859 A (DAVID C. FELDMEIER), 10 December 1996 (10.12.96), column 3, line 45 - column 4, line 16, claims 1-17  --	1-14
A	EP 0786919 A1 (INTERNATIONAL BUSINESS MACHINES CORPORATION), 30 July 1997 (30.07.97), claims 1-13  --	1-14
A	US 5333135 A (JAMES W. WENDORF), 26 July 1994 (26.07.94), column 4, line 24 - column 5, line 6, figure 2  --	1-14
A	US 5737332 A (RICHARD J. CORRIGAN ET AL), 7 April 1998 (07.04.98), column 2, line 36 - line 53, figure 2, claims 1-11  -- -----	1-14

**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

02/12/99

International application No.  
PCT/FI 99/00821

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
US	5570362	A	29/10/96	JP	7254904 A	03/10/95
WO	9738550	A1	16/10/97	AU	2417197 A	29/10/97
				CA	2251375 A	16/10/97
				CN	1221548 A	30/06/99
				EP	0893037 A	27/01/99
				US	5822321 A	13/10/98
US	5583859	A	10/12/96	NONE		
EP	0786919	A1	30/07/97	JP	9233127 A	05/09/97
				US	5930265 A	27/07/99
US	5333135	A	26/07/94	CA	2114182 A	02/08/94
				DE	69415698 D,T	22/07/99
				EP	0609936 A,B	10/08/94
				JP	6291780 A	18/10/94
				MX	9400775 A	31/08/94
US	5737332	A	07/04/98	AU	1350897 A	22/08/97
				BR	9607801 A	07/07/98
				DE	19681312 T	16/04/98
				GB	2314490 A	24/12/97
				GB	9720589 D	00/00/00
				IL	119892 D	00/00/00
				WO	9728627 A	07/08/97